

DECKfon[®] 37T & Quattro 39

Direct to Joist Structural Deck Acoustic Floorboards



Product Information

CELLECTA DECKfon[®] structural acoustic composite floorboards are designed to be laid directly on the floor joists to provide outstanding sound proofing.

37T is designed for timber floors where a new ceiling is to be installed.

Quattro 39 is for floors where the existing ceiling is retained.

Product Benefits

- Excellent acoustic performance
- Two types available: **37T** (37mm) and **Q39** (39mm)
- Incorporate moisture resistant structural floorboard
- Recycled resilient layer
- Quick and easy to install

Technical Data

		DECKfon [®]	
		37T	Quattro 39
Product description	-	Direct to joist, two layer composite acoustic structural floorboard	Direct to joist, four layer composite acoustic structural floorboard
Overall thickness	mm	37	39
Type of facing board	-	22mm P5 chipboard	18mm P5 chipboard
Resilient layer(s)	-	15mm open-cell PU foam*	3mm fleece & 8mm fleece
Board dimensions	mm	600 x 2400	600 x 2400
Weight	kg/m ² kg/board	16.70 24.05	20.95 30.17
Associated flanking strip required	-	YELOfon ES5/100	YELOfon ES5/100

Third Party Accreditation and Approvals



Environmental Credentials

